

FOUNDATION SUPPORTWORKS[®]

SOLUTIONS FOR EXTREME WALL PROBLEMS

Geo-Lock™ Channel Anchors for Permanent Stabilization



ADVANTAGES

- ✓ Zinc-plated components prevent rust (unlike painted or uncoated systems that can flake and rust over time).
- ✓ Immediately stabilize walls that are pushing in at the bottom.
- ✓ Channel connects to an earth anchor embedded deep into stable soil.
- ✓ Installations can usually be completed in less than one day.
- ✓ Zinc-plated channels provide a neat and clean look.



Extreme Wall Problems

SOLUTIONS FOR EXTREME WALL PROBLEMS

Soil Removal and Immediate Wall Straightening



Basement wall severely tipping in at the top.



Wall is immediately returned to its original position after soil is removed and **Geo-Lock™ Anchors** are installed.

ADVANTAGES



Can solve even the worst foundation wall problems



Immediate stabilization and straightening of the wall



Block wall pushing in several inches at the bottom.



After excavation of soil, the wall is stabilized and returned to a straight position.

MOISTURE BARRIER

With the soil excavated from around your foundation wall, it is the perfect opportunity to have the **TAMKO™ TW-60** waterproofing membrane installed to guard against water seepage through any cracks in your basement wall.

